

Crunch Oil[®]

HYDROCARBON ABSORBENTS



NEGOCIOS GLOBALES SA
9 de Julio N° 1189 Floor 1 Of. N° 9
Tel: 00 54 261 4230482

ABSORBENT PAD WITH A WATERPROOF SURFACE



The CRUNCHOIL hydrocarbon absorbent pads with waterproof face are made of inert synthetic fibres, principally composed of polypropylene and a low-density polyethylene sheet. The pads have been designed to absorb hydrocarbons-based liquids, and they repel these water-based products, thanks to their waterproof characteristic, which also allows them to float.

It is a product specially-designed to be used for hydrocarbons leaks and spills, where the released substance will be absorbed by the synthetic fibres, while being completely isolated from the soil, thanks to its polyethylene surface (waterproof), thus avoiding pollution.



APPLICATIONS

Spills, leaks in equipment and machinery in all types of industries, factories and workshops. Containment of small, medium and large spills of oils and any type of hydrocarbons and non-polar organic solvents such as: paraffin, diesel oil, alcohols, toluene, ethers and esters.

PRESENTATION

Code	Product	Dimensions	Weight
	Pkg of 100 pads	50cm x 50cm	3kg
	Pad Roll (120gr)	50cm x 50m	3kg
	Pad Roll (120gr)	1m x 50m	6kg
	Pad Roll (120gr)	2m x 50m	12kg

CHARACTERISTICS

- Color: White
- Longitudinal Resistance: 20N/5cm
- Longitudinal Elongation: >10%
- Transversal Resistance: > 20 /5cm
- Transversal Elongation: >30%
- Absorption Rate: MC120=9.8

LIMITATIONS

Usage with strong oxidants is not recommended. A compatibility test is recommended before using the absorbent with the liquid in question. If it is going to be used at temperatures above 100°C, it is essential to perform this test before proceeding with the absorption.

FINAL DISPOSAL

Once contaminated, the ABSORBENT PAD can be sent to final disposal through incineration or landfills according to the legislation of each site. In most cases, recovery of a significant fraction of the product absorbed is possible.