

Crunch Oil[®]

HYDROCARBON ABSORBENTS



NEGOCIOS GLOBALES SA
9 de Julio N° 1189 Floor 1 Of. N° 9 - Mendoza, Argentina
Tel: 00 54 261 4230482

UNIVERSAL ABSORBENT PADS



CRUNCHOIL UNIVERSAL ABSORBENT PADS are made of small polypropylene microfibers with high absorbing properties and low waste generation.

The pads have been designed to absorb a large amount of liquids, such as acids, alkalis, hydrocarbons, solvents, etc.

UNIVERSAL ABSORBENT PADS have sufficient capacity to handle acids, bases, coolants and most hazardous fluids. They can also be used to absorb oil and aqueous liquids. These pads do not react to most liquid chemical compounds.

LIMITATIONS

Usage with strong oxidants is not recommended. A compatibility test is recommended before using the absorbent with the liquid in question. If it is going to be used at temperatures above 100°C, it is essential to perform this test before proceeding with the absorption.

PRESENTATION

Code	Product	Dimensions	Weight
111271	Pkg 100 pads (160 gr)	50 cm x 50 cm	4 kg
	Pad Roll (160gr)	50 cm x 50 m	4 kg

APPLICATIONS

Spills, leaks in equipment and machinery in all types of industries, factories and workshops.
Containment of small and large spills of oils, acids, alkalis, and any hazardous fluid.

Control, cleaning and recovery of liquids derived from hydrocarbons and chemicals in general, in any type of terrain.

PHYSICAL AND CHEMICAL PROPERTIES

	PROPERTIES		ANALYSIS	
		Units	Average	
Grammage	160 g/m ²	+/- 5%		
Resistance MD	N/5cm	<70		
Elongation MD	%	<40		
Resistance CD	N/5cm	<65		
Elongation CD	%	<60		
Air permeability	L/m ² . S	20 - 180		

FINAL DISPOSAL

Once contaminated, the ABSORBENT PAD can be sent to final disposal through incineration or landfills according to the legislation of each site.
In most cases, recovery of a significant fraction of the absorbed product is possible.